

DYNAVOICE

EXPERIENCE THE NORDIC SOUND

The DF-8II elevates our most powerful floorstander offering an expansive soundstage, deeper bass, and enhanced accuracy.

A 35mm front and back, 15mm side panels, and multiple internal bracing create a rigid, resonance-free cabinet. They feature dual 8" resin-coated Kevlar™ bass drivers, a 6.5" Kevlar™ midrange, and a combined soft dome/ribbon tweeter for dynamic, detailed sound.

The Dynavoice X-Change bi-wire terminals with gold-plated connectors enable midrange fine-tuning for a personalized listening experience.

PRODUCT SPECIFICATIONS

Type:	Four-way bass reflex floorstanding speaker.
Speaker drivers:	Woofer: 2pcs Ø178mm Kevlar cone Midrange: 1pc Ø142mm Kevlar cone Tweeter: 1pc Ø36mm Silk dome Tweeter: 1pc 18x50mm Ribbon
Sensitivity (1W/1M):	94dB
Power handling:	200W (RMS)
Rec. amplifier power:	40-250W (RMS)
Nominal impedance:	6 Ohm
Minimum impedance:	3.4 Ohm
Frequency response:	23 - 32000 Hz
Crossover Frequency:	370 / 3200 / 12800 Hz
Net weight (each):	28.5 kg



DEFINITION

DF-8II

Available colors:



RESEARCHED & DESIGNED
IN SWEDEN



Dynavoice, a part of Winn Scandinavia AB
www.facebook.com/dynavoice | www.dynavoice.se